Automation Aides
Torque & Assembly Tool Experts Since 1952
26 EVERGREEN AVE., WARMINSTER, PA 18974 PHONE (215)956-1971 FAX (215)956-1975 EMAIL INFO@AUTOAIDES.COM
autoaides.com

Atlas Copco

Model	Torque range soft joint Nm	Torque range soft joint in lb	Free speed r/min	Weight kg	Weight lb	Length mm	Angle head height mm	Angle head centre to side mm	Air consumption at free speed l/s	Air consumption at free speed cfm	Rec. hose size mm	Air inlet thread in	Sound level dB(A)	Ordering No.
Air shut-off control models														
LTV009 R025-Q	0.6 - 2.5	5.3 - 22.1	1650	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 00
LTV009 R025-42	0.6 - 2.5	5.3 - 22.1	1650	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 01
LTV009 R025-6	0.6 - 2.5	5.3 - 22.1	1650	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 02
LTV009 R03-10	0.7 - 3	6.2 - 26.5	1400	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 23
LTV009 R035-Q	0.4 - 3.5	3.5 - 31	1100	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 03
LTV009 R035-42	0.4 - 3.5	3.5 - 31	1100	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 04
LTV009 R035-6	0.4 - 3.5	3.5 - 31	1100	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 05
LTV009 R05-Q	0.4 - 5	3.5 - 44.2	850	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 06
LTV009 R05-42	0.4 - 5	3.5 - 44.2	850	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 07
LTV009 R05-6	0.4 - 5	3.5 - 44.2	850	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 08
LTV009 R07-Q	1.1 - 7	9.7 - 61.9	500	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 09*
LTV009 R07-42	1.1 - 7	9.7 - 61.9	500	0.7	1.5	266	25	9	6	13	6	1/8	76	8431 0278 10*
LTV009 R07-6	1.1 - 7	9.7 - 61.9	500	0.7	1.5	266	28.5	11	6	13	6	1/8	76	8431 0278 11*
LTV009 R08-6-200	1.3 - 9	11.5 - 79.6	200	0.7	1.5	266	28.5	11	6	13	6	1/8	76	8431 0278 24*
LTV009 R09-Q	1.3 - 9	11.5 - 79.6	430	0.7	1.5	266	28.5	11	6	13	6	1/8	76	8431 0278 12
LTV009 R09-10	1.3 - 9	11.5 - 79.6	430	0.7	1.5	266	28.5	11	6	13	6	1/8	76	8431 0278 13
LTV009 R09-42	1.3 - 9	11.5 - 79.6	430	0.7	1.5	266	28.5	11	6	13	6	1/8	76	8431 0278 15
LTV009 R09-42M	1.3 - 9	11.5 - 79.6	430	0.7	1.5	266	28.5	11	6	13	6	1/8	76	8431 0278 16
LTV009 R09-6	1.3 - 9	11.5 - 79.6	430	0.7	1.5	266	28.5	11	6	13	6	1/8	76	8431 0278 17
LTV009 R11-Q	1.3 - 11	11.5 - 97.3	320	0.8	1.8	266	28.5	11	6	13	6	1/8	76	8431 0278 19*
LTV009 R11-10	1.3 - 11	11.5 - 97.3	320	0.8	1.8	266	28.5	11	6	13	6	1/8	76	8431 0278 20*
LTV009 R11-42	1.3 - 11	11.5 - 97.3	320	0.8	1.8	266	28.5	11	6	13	6	1/8	76	8431 0278 21*
LTV009 R11-6	1.3 - 11	11.5 - 97.3	320	0.8	1.8	266	28.5	11	6	13	6	1/8	76	8431 0278 22*
Air shut-off control models														
LTV008 R09-10-220	1.3 - 9	11.5 - 79.6	220	0.8	1.8	285	28.5	11	6	13	6	1/8	76	8431 0281 39
LTV008 R09-6-70	1.3 - 9	11.5 - 79.6	70	0.8	1.8	285	28.5	11	6	13	6	1/8	76	8431 0281 46
LTV008 R11-6-100	1.3 - 11	11.5 - 97.3	100	0.8	1.8	285	28.5	11	6	13	6	1/8	76	8431 0280 29
LTV008 R11-6-50	1.3 - 11	11.5 - 97.3	50	0.8	1.8	285	28.5	11	6	13	6	1/8	76	8431 0280 30
LTV08 R03-6	0.5 - 3.2	4.4 - 26	1000	0.8	1.7	275	28.5	10	4	8	6	1/8	69	8431 0325 88
LTV08 R03-42	0.5 - 3.2	4.4 - 26	1000	0.8	1.7	275	28.5	10	4	8	6	1/8	69	8431 0325 84
LTV08 R03-Q	0.5 - 3.2	4.4 - 26	1000	0.8	1.7	275	28.5	10	4	8	6	1/8	69	8431 0325 92
LTV08 R05-6	0.5 - 4.5	4.4 - 39	700	0.8	1.7	275	28.5	10	4	8	6	1/8	69	8431 0325 78
LTV08 R05-42	0.5 - 4.5	4.4 - 39	700	0.8	1.7	275	28.5	10	4	8	6	1/8	69	8431 0325 74
LTV08 R05-Q	0.5 - 4.5	4.4 - 39	700	0.8	1.7	275	28.5	10	4	8	6	1/8	69	8431 0325 81
LTV18 R07-6	3.5 - 7	31 - 61	700	1.2	2.6	290	28.5	10	6	13	6	1/4	71	8431 0326 72*
LTV18 R07-42	3.5 - 7	31 - 61	700	1.2	2.6	290	28.5	10	6	13	6	1/4	71	8431 0326 61
LTV18 R07-Q	3.5 - 7	31 - 61	700	1.2	2.6	290	28.5	10	6	13	6	1/4	71	8431 0326 76
LTV18 R15-6	6.0 - 15	53 - 132	360	1.2	2.6	308	28	11	7	15	8	1/4	71	8431 0326 55
LTV18 R15-10	6.0 - 15	53 - 132	360	1.2	2.6	308	28	11	7	15	8	1/4	71	8431 0326 56*
LTV18 R15-42	6.0 - 15	53 - 132	360	1.2	2.6	308	28	11	7	15	8	1/4	71	8431 0326 54
LTV18 R15-Q	6.0 - 15	53 - 132	360	1.2	2.6	308	28	11	7	15	8	1/4	71	8431 0326 58
Slip clutch models with 1/4" square drive														
TWIST VR07-6	1.3 - 7.0	12 - 62	700	1.0	2.2	280	29	10	4	8	8	1/4	72	8431 0256 11*
TWIST VR13-6	2.0 - 6.0	18 - 53	1300	1.0	2.2	280	29	10	4	8	8	1/4	72	8431 0256 37
Slip clutch models with 1/4" female hexagon drive														
TWIST VR07-I6	1.3 - 7.0	12 - 62	700	1.0	2.2	280	29	10	4	8	8	1/4	72	8431 0256 03*
TWIST VR13-I6	2.0 - 6.0	18 - 53	1300	1.0	2.2	280	29	10	4	8	8	1/4	72	8431 0256 29

ESD approved: LTV008/009.

All models: Are reversible.

-42 = 1/4" female hexagon drive for bits.

-10 = 3/8" square drive.

-6 = 1/4" square drive for sockets.

-Q = 1/4" quick change chuck.

* Basic tools of the range, cover most needs.