

# Impact Wrenches

Capacity 3/16" - 7/8"



S2480/S2481



W2110/W2111



W2210A/W2211



W2216



W2216 KIT



W2219

Model	Bolt size in	Square drive in	Max torque fwd ft lb	Recommended torque range ft lb	Free speed rpm	Weight lb	Length in	Air consumption cfm	Rec. Hose size in	Air inlet thread in	Ordering No.
S2480	3/16	1/4 HEX QC	15	4-10	6,500	1.7	5.2	21.2	1/4	1/4	8431 0257 90
S2481	1/4	1/4 HEX QC	21	8-15	5,000	1.9	5.6	17	1/4	1/4	8431 0257 92
W2110	1/2	1/4 HEX QC	69	9-50	8,000	2.2	6.3	18.4	3/8	1/4	8434 1244 20
W2111	1/2	3/8	69	9-50	8,000	2.2	6.1	18.4	3/8	1/4	8334 1244 23
W2210A	9/16	3/8	199	50-130	9,000	3.7	6.3	18.4	3/8	1/4	8434 1244 31
W2211	9/16	1/2	199	50-130	9,000	3.7	6.3	24.6	3/8	1/4	8434 1244 33
W2216	5/8	1/2	530	110-470	7,000	5.5	7.7	24.6	3/8	1/4	8434 1244 75
W2216 KIT*	5/8	1/2	530	110-470	7,000	5.5	7.7	24.6	3/8	1/4	8434 1244 76
W2219	7/8	3/4	700	330-520	3,800	112	10	25.8	3/8	1/4	8434 1244 37

\* Sockets included 13, 15, 17, 19, 24 in.