

Screwdrivers

Impact drive



S2480/S2481

Model	Screw size in	Torque range ft lb	Free speed rpm	Weight lb	Length in	Air consumption cfs	Rec. Hose size in	Air inlet thread in	Ordering No.
S2480	3/16	4.4-9.6	6,500	1.7	5.2	21.2	3/8	1/4	8431 0257 90
S2481	1/4	8.1-14.8	5,000	1.9	5.6	17	3/8	1/4	8431 0257 92

Direct drive



S2305/S2326

Model	Screw size in	Torque range ft lb	Free speed rpm	Weight lb	Length in	Air consumption cfm	Rec. Hose size in	Air inlet thread in	Ordering No.
S2305	5/16	0-8.9	750	2	7.8	11.9	1/4	1/4	8431 0257 28
S2326	1/4	0-3.3	2,400	1.8	7	11.9	1/4	1/4	8431 0257 36

Slip-clutch



S2308-C/S2309-C/S2310-C

Model	Screw size in	Torque range ft lb	Free speed rpm	Weight lb	Length in	Air consumption cfm	Rec. Hose size in	Air inlet thread in	Ordering No.
S2308-C	1/4	1.8-8.1	950	2.4	8.9	17.8	3/8	1/4	8431 0257 20
S2309-C	3/16	1.1-5.5	1,200	2.2	9.6	14.8	3/8	1/4	8431 0257 22
S2310-C	5/16	1.5-11.1	800	2.4	8.9	18	3/8	1/4	8431 0257 24