

## Slip-clutch



**S2340-C/S2360-C/S2370-C**

Model	Screw size in	Torque range ft lb	Free speed rpm	Weight lb	Length in	Air consumption cfm	Rec. Hose size in	Air inlet thread in	Ordering No.
S2340-C	1/8	0.4-1.5	1,300	2	9.8	8.5	1/4	1/4	8431 0257 40
S2360-C	5/32-3/16	1-5.2	700	2	10.2	8.5	1/4	1/4	8431 0257 60
S2370-C	3/16	1.5-4.4	1,300	2	9.8	8.5	1/4	1/4	8431 0257 70

## Shut-off



**S2450-P/S2451-P/S2452-P**

Model	Screw size in	Torque range ft lb	Free speed rpm	Weight lb	Length in	Air consumption cfm	Rec. Hose size in	Air inlet thread in	Ordering No.
S2450-P	3/16	1.8-3.7	1,100	2.4	8.7	26.9	3/8	1/4	8431 0257 84
S2451-P	3/16	2.6-5.5	800	2.4	9.8	31.4	3/8	1/4	8431 0257 86
S2452-P	1/4	2.6-8.9	580	2.4	9.8	31.4	3/8	1/4	8431 0257 87

## Shut-off



**S2416-L/2426-L/2428-L**

Model	Screw size in	Torque range ft lb	Free speed rpm	Weight lb	Length in	Air consumption cfm	Rec. Hose size in	Air inlet thread in	Ordering No.
S2416-L	1/8	0.4-1.2	1,500	2	9.1	12.7	3/8	1/4	8431 0257 82
S2426-L	5/32	0.9-1.9	1,500	2	9.1	12.7	3/8	1/4	8431 0257 80
S2428-L	3/16	2.6-5.2	700	2.4	9.5	12.7	3/8	1/4	8431 0257 81